



GRILL SMART WITH MAVERICK



Chefs and BBQ Pitmasters choose Maverick Thermometers for their advanced features, reliability and outstanding accuracy.

To ensure your food is cooked to perfection every time, always 'Grill Smart with Maverick'.

### DT-09C

#### EASY READ DIGITAL THERMOMETER SINGLE PROBE

Features:

- Accurate temperature read in less than 4 seconds.
- Temp Range: -50°C to 300°C.
- Auto shut off after 10 minutes.
- Thermometer cover comes with a cord to hang around your neck or from a hook.
- Detachable cover doubles as a handle.
- Water resistant but NOT dishwasher safe.
- 1 LR44 battery included.



### LT-04

#### LASER INFRARED SURFACE THERMOMETER

Features:

- Simply aim the laser and press the trigger to measure your cooking surface temperature.
- Measures temperature without contact.
- Instant readings in °C or °F.
- Temp Range: -42°C to 550°C[-44°F to 1022°F].
- Large bright LCD with backlight.
- Check for Hot / Cool spots.
- Accurate up to 1.5m away.
- 1 - 9 Volt Battery included.



### PT-50

#### 2 WAY THERMOCOUPLE SINGLE FOLDING PROBE

Features:

- Right or Left Hand Display options.
- Displays in both °C and °F.
- Temp Range: -40°C to 350°C[-40°F to 660°F].
- Display rotates 180° for easy viewing.
- Accurate Temp in less than 5 seconds.
- Super thin tip for easy measurement.
- Turns on automatically when probe is opened and shuts off when closed.
- LCD back light for night time viewing.
- 2 AAA batteries included.



### PT-100

#### PRO-TEMP THERMOCOUPLE SINGLE FOLDING PROBE

Features:

- Type K thermocouple with integral stainless precision micro-tip probe.
- Temperature Range: -40°C to 230°C.
- Turns ON/OFF automatically when the probe is pivoted.
- Easy release carabiner belt clip.
- Low battery indicator and handy auto power save after 5 minutes of inactivity.
- Handy cooking chart on unit body.
- 3 AAA batteries included.



## XR-40

### EXTENDED RANGE WIRELESS REMOTE DUAL PROBE

#### Features:

- Remotely monitor temperatures from up to 500 ft away, making this one of the most sought-after grill accessories.
- Receive temperature readings using the included 2 meat probes.
- Meat thermometer alerts you if the temperatures go above or below your programmed range.
- With 500 ft range line of sight the XR-40 breaks records! MUCH better range than the typical 150-300 ft!
- The improved LCD screen on the digital thermometer also comes with orange reverse text for easy readings, no matter whether you're grilling during the day or at night.



## ET-733

### REMOTE BBQ THERMOMETER DUAL PROBE

#### Features:

- Includes a transmitter, receiver, two hybrid probes and two handy grill clips.
- Temp Range: 0°C to 300°C.
- Long probe wires rated to 380°C.
- Receiver stores settings even when off.
- 15 preset temperatures.
- Audio alarm alert when a pre-set temp is reached.
- Loss of signal alerts if out of range.
- 4 AAA batteries included.



## BB-44

### EXTENDED RANGE WIRELESS REMOTE SINGLE PROBE

#### Features:

- Remote BBQ thermometer with single probe included with the product.
- 90m range, C° or F°.
- Water resistant probe and rated to 350°C (662F°).
- Controls on transmitter; alarm on/off receiver.
- Simply programmable for 9 meat types: poultry, fish, ground poultry, ground beef, veal, beef, chicken, pork, and lamb.



## BT-600

### iCHEF EXTENDED RANGE DUAL PROBE BLUETOOTH

#### Features:

- Water-resistant transmitter that monitors up to four probes at one time.
- Displays in F° or C°.
- Temp Range: High Temp 60C° to 300C°(140°F to 572°F); Low Temp 0C° to 290C°(32°F to 554°F).
- Food range -20C° to 300C°(-4°F to 572°F)
- Options to monitor: one meat and one BBQ, two meats, or two BBQs.
- Preset food temps for Beef, Veal, Lamb, Pork, Chicken, Turkey and for various game meats.
- 91m range with alert for loss of signal and target food temp are reached.
- Requires two AAA batteries not included.



## XR-50

### REMOTE BBQ THERMOMETER - FOUR PROBES

#### Features:

- Remote BBQ thermometer with four probes included.
- 160m range, C° or F°.
- Water resistant probes and rated to 380°C (716F°).
- LCD backlighting on ALL probes.
- Can set HIGH or LOW alarms for each probe.
- Controls on transmitter; alarm on/off receiver.
- Simple programming, fast connection and reduced connection drop-outs.

